




















GLOBAL LUX INC. TRIPLLED

 90 mm	 35x26x17	 PWM	 iP 65
 2 ans	 12V DC	 RADIAL	 120°
 100 modules	 -25 à +45	 1 modules	 100 max



Caractéristiques

Réf.	Couleurs	Protection	Flux (lm)	Puissance (W)	Angle d'ouverture
YA-TRI 30	Blanc 3000°K	65	11	0.22	120°
YA-TRI 70	Blanc 7000°K	65	11	0.22	120°
YA-TRI 80	Blanc 8000°K	65	11	0.22	120°
YA-TRI AM	 Ambre	65	6	0.35	120°
YA-TRI BL	 Bleu	65	6	0.22	120°
YA-TRI OR	 Orange	65	6	0.35	120°
YA-TRI PI	 Pink	65	6	0.35	120°
YA-TRI RO	 Rouge	65	6	0.35	120°
YA-TRI VE	 Vert	65	15	0.22	120°

Alimentations

Couleur	Alimentations	Nombre de modules	Modules max
TRIPLELED	60 W (e)	230	100
	100 W (e)	380	100
	150 W (e)	570	100



Applications

Pour petites à moyennes enseignes à points lumineux apparents

Chaîne Tripleled. Perçage tôle : 5 mm (+/- 0,2 mm). Épaisseur tôle : 1 mm à 4 mm.